

Modern and ecological street lighting.

Astreet LED is professional fixture equipped in LED light sources - CREE diodes with high light efectiveness.





ASTREET LED

Solid opening bucket.



Powder coated housing. Upper unit with grey color (RAL 7045) and lower with white colour (RAL 9016).




Lampshade made of OptiWhite (TM) tempered

small losts.

Hight light permeability =

Mechanical resistance IK10 - unique damage strenght.

Exemplary light distribution for Astreet LED 50.





Included allen wrench keys and adjustable (+/- 90°) grip to fasten fixture on pole Ø 60 mm.






ASTREET LED

Light sources are also available as separate product.

Parameters:

Power source 7W, electricity 350mA, power supply 20V.



Astreet LED

Model	Catalogue number	Power	Luminous flux*	Source of light	Basic dimension
Astreet LED 20	97365	18 W	2050 lm / 1875 lm	LED 14 W (2 x 7 W)	468 x 235 x 101 mm
Astreet LED 30	97366	27 W	3075 lm / 2825 lm	LED 21 W (3 x 7 W)	468 x 235 x 101 mm
Astreet LED 40	97836	36 W	4100 lm / 3750 lm	LED 28 W (4 x 7 W)	468 x 235 x 101 mm
Astreet LED 50	97837	45 W	5125 lm / 4700 lm	LED 35 W (5 x 7 W)	468 x 235 x 101 mm
Astreet LED DIM 20	97217	18 W	2050 lm / 1875 lm	LED 14 W (2 x 7 W)	468 x 235 x 101 mm
Astreet LED DIM 30	97218	27 W	3075 lm / 2825 lm	LED 21 W (3 x 7 W)	468 x 235 x 101 mm
Astreet LED DIM 40	97219	36 W	4100 lm / 3750 lm	LED 28 W (4 x 7 W)	468 x 235 x 101 mm
Astreet LED DIM 50	97305	45 W	5125 lm / 4700 lm	LED 35 W (5 x 7 W)	468 x 235 x 101 mm

^{*} LED source data without and with diffuser

Astreet LED light sources

Catalogue number	Power	Colour temperature *
97827	7 W	4200 K
97089	7 W	6300 K

^{*} Other colour temperatures on requeste





